CSc 453 — Compilers and Systems Software

15 : Intermediate Code III

Christian Collberg
Department of Computer Science
University of Arizona
collberg@gmail.com

October 18, 2009

1

Basic Blocks and Flow Graphs

2 Control Flow Graphs

- We divide the intermediate code of each procedure into basic blocks. A basic block is a piece of straight line code, i.e. there are no jumps in or out of the middle of a block.
- The basic blocks within one procedure are organized as a *(control) flow graph*, or *CFG*. A flow-graph has
  - basic blocks $B_1 \cdots B_n$ as nodes,
  - a directed edge $B_1 \rightarrow B_2$ if control can flow from B_1 to B_2.
  - Special nodes $\boxed{\texttt{ENTER}}$ and $\boxed{\texttt{EXIT}}$ that are the *source* and *sink* of the graph.
- Inside each basic block can be any of the IRs we've seen: tuples, trees, DAGs, etc.

3



4 Control Flow Graphs...

Source Code:

```
X := 20; WHILE X < 10 DO
   X := X-1; A[X] := 10;
   IF X = 4 THEN X := X - 2; ENDIF;
ENDDO; Y := X + 5;
```

Intermediate Code:

```
(1) X := 20                (5) if X<>4 goto (7)
(2) if X>=10 goto (8)      (6) X := X-2
(3) X := X-1               (7) goto (2)
(4) A[X] := 10             (8) Y := X+5
```

5 Control Flow Graphs...

Flow Graph:



6



7

Constructing Basic Blocks

8 Constructing Basic Blocks

- Assume that the input is a list of tuples. How do we find the beginning and end of each basic block?

1. First determine a set of **leaders**, the first tuple of basic blocks:
   (a) The first tuple is a leader.
   (b) Tuple `L` is a leader if there is a tuple `if ...goto L` or `goto L`.
   (c) Tuple `L` is a leader if it immediately follows a tuple `if ...goto B` or `goto B`.
2. A basic block consists of a leader and all the following tuples until the next leader.

9 Basic Blocks...

```
P := 0; I := 1;
REPEAT
   P := P + I;
   IF P > 60 THEN
      P := 0;
      I := 5
   ENDIF;
   I := I * 2 + 1;
UNTIL I > 20;
K := P * 3
```

```
(1)   P := 0          ⇐ (Rule 1.a)
(2)   I := 1
(3)   P := P + I      ⇐ (Rule 1.b)
(4)   IF P <= 60 GOTO (7)
(5)   P := 0          ⇐ (Rule 1.c)
(6)   I := 5
(7)   T1 := I * 2     ⇐ (Rule 1.b)
(8)   I := T1 + 1
(9)   IF I <= 20 GOTO (3)
(10)  K := P * 3      ⇐ (Rule 1.c)
```

10 Basic Blocks...

B_1: `[(1) P:=0; (2) I:=1]`
B_2: `[(3) P:=P+I;`
`(4) IF P<=60 GOTO` $\boxed{B_4}$`]`
B_3: `[(5) P:=0; (6) I:=5]`
B_4: `[(7) T1:=I*2; (8) I:=T1+1;`
`(9) IF I<=20 GOTO` $\boxed{B_2}$`]`
B_5: `[(10) K:=P*3]`



11

Summary

12 Readings and References

- Read Louden:

  Flow Graphs 475–477

- Or, read the Dragon book:

  Basic Blocks 528–530

  Flow Graphs 532–534

13 Summary

- A Control Flow Graph (CFG) is a graph whose nodes are basic blocks. There is an edge from basic block B_1 to B_2 if control can flow from B_1 to B_2.
- Control flows in and out of a CFG through two special nodes `ENTER` and `EXIT`.
- We construct a CFG for each procedure. This representation is used during code generation and optimization.
- Java bytecode is a stack-based IR. It was never intended as an UNCOL, but people have still built compilers for Ada, Scheme and other languages that generate Java bytecode. It is painful.
- Microsoft's MSIL is the latest UNCOL attempt.

14

Homework

15 Homework I

Translate the program below into quadruples. Identify beginnings and ends of basic blocks. Build the control flow graph.

```
PROGRAM P;
VAR X : INTEGER; Y : REAL;
BEGIN
   X := 1; Y := 5.5;
   WHILE X < 10 DO
      Y := Y + FLOAT(X);
      X := X + 1;
      IF Y > 10 THEN Y := Y * 2.2; ENDIF;
   ENDDO;
END.
```

16 Exam Question

- Draw the control flow graph for the tuples.

```
int A[5],x,i,n;
for (i=1; i<=n; i++) {
  if (i<n) {
    x = A[i];
  } else {
    while (x>4) {
      x = x*2+A[i];
    };
  };
  x = x+5;
}
```

```
(1) i := 1
(2) IF i>n GOTO (14)
(3) IF i>=n GOTO (6)
(4) x := A[i]
(5) GOTO (11)
(6) IF x<=4 GOTO (11)
(7) T1 := x*2
(8) T2 := A[i]
(9) x := T1+T2
```

```
(10)  GOTO (6)
(11)  x := x+5
(12)  i := i+1
(13)  GOTO (2)
```