

CSc 520

Principles of Programming Languages

27: Control Structures — Procedures

Christian Collberg

collberg+520@gmail.com

Department of Computer Science
University of Arizona

Copyright © 2008 Christian Collberg

—Spring 2008 — 27

[1]

Procedures as Control Abstractions

- A procedure is a collection of computation (expressions, statements, etc).that we can give a name.
- A **call-site** is a location where a **caller** invokes a procedure, the **callee**.
- The caller waits for the callee to finish executing, at which time controls to the point after the call-site.
- Most procedures are **parameterized**. The values passed to the procedure are called **actual parameters**.
- The actual parameters are mapped to **formal parameters**, which hold the actual values within the procedure.

520 —Spring 2008 — 27

[2]

Procedures as Control Abstractions...

- Some procedures (called functions) return a value. In some languages, a function can return multiple values.
- Most languages use a **call-stack** on which actual parameters and local variables are stored.
- Different languages have different rules as to how parameters should be passed to a procedure.

—Spring 2008 — 27

[3]

Questions

- How do we deal with recursion? Every new recursive call should get its own set of local variables.
- How do we pass parameters to a procedure?
 - Call-by-Value or Call-by-Reference?
 - In registers or on the stack?
- How do we allocate/access local and global variables?
- How do we access non-local variables? (A variable is non-local in a procedure P if it is declared in procedure that statically encloses P.)
- How do we pass large structured parameters (arrays and records)?

520 —Spring 2008 — 27

[4]

Case Study — Pascal

Pascal Procedures

```
PROCEDURE Name (list of formals);  
    CONST (* Constant declarations *)  
    TYPE (* Type declarations *)  
    VAR (* Variable declarations *)  
        (* Procedure and function definitions *)  
BEGIN  
    (* procedure body *)  
END;
```

- Note the similarity with the program structure.
- Note that procedures can be nested.
- Note the semicolon after the end.

Pascal Procedures...

- Formal parameters look like this:

procedure name (formal1:type1; formal2:type2;..
 or like this
procedure name (formal1,formal2...:type1; ...);

- By default, arguments are **passed by value**. **var** indicates that they are **passed by reference**:

procedure name (var formal1:type1; ...);

Pascal Procedures...

- Functions are similar to procedures but return values:

```
function func1 (formals);  
begin  
    func1 := 99;  
end;
```

- To return a value assign it to the function name.

Pascal Procedures...

- Procedures can be nested:

```
procedure A ();  
  procedure B();  
  begin  
    ...  
  end;  
begin  
  ...  
end;
```

- Names declared in an outer procedure are visible to nested procedures unless the name is redeclared.

Pascal Procedures...

- Procedures can be recursive. The **forward** declaration is used to handle mutually recursive procedures:

```
procedure foo (); forward;  
  
procedure bar ();  
begin  
  foo();  
end;  
  
procedure foo();  
begin  
  bar();  
end;
```

Case Study — Ada

Ada — Subprogram Declarations

```
procedure Traverse_Tree;  
procedure Increment(X : in out Integer);  
procedure Right_Indent(Margin : out Line_Size);  
procedure Switch(From, To : in out Link);  
  
function Random return Probability;  
  
function Min_Cell(X : Link) return Cell;  
function Next_Frame(K : Positive) return Frame;  
function Dot_Product(Left, Right : Vector)  
  return Real;
```

Ada — Subprogram Declarations

```
function "*" (Left, Right : Matrix) return Matrix;
```

• Examples of in parameters with default expressions:

```
procedure Print_Header(Pages : in Natural;  
    Header : in Line :=  
        (1 .. Line'Last => ' ');  
    Center : in Boolean := True);
```

Ada — Subprogram Bodies

-- Example of procedure body:

```
procedure Push(E : in Element_Type;  
    S : in out Stack) is  
begin  
    if S.Index = S.Size then  
        raise Stack_Overflow;  
    else  
        S.Index := S.Index + 1;  
        S.Space(S.Index) := E;  
    end if;  
end Push;
```

Ada — Procedure Call

```
Traverse_Tree;  
Print_Header(128, Title, True);  
  
Switch(From => X, To => Next);  
Print_Header(128, Header => Title,  
    Center => True);  
Print_Header(Header=>Title,  
    Center=>True, Pages=>128);
```

--Examples of function calls:

```
Dot_Product(U, V)  
Clock
```

Ada — Procedure Call

-- Procedures with default expressions:

```
procedure Activate(  
    Process : in Process_Name;  
    After    : in Process_Name:=No_Process;  
    Wait     : in Duration := 0.0;  
    Prior    : in Boolean := False);  
  
procedure Pair(Left, Right :  
    in Person_Name:=new Person);
```

Ada — Procedure Call...

```
-- Examples of their calls:
Activate(X);
Activate(X, After => Y);
Activate(X, Wait => 60.0, Prior => True);
Activate(X, Y, 10.0, False);
Pair;
Pair(Left => new Person, Right => new Person);
```

Ada — Overloaded Calls

```
procedure Put(X : in Integer);
procedure Put(X : in String);

procedure Set(Tint : in Color);
procedure Set(Signal : in Light);
```

```
-- Examples of their calls:
Put(28);
Put("no possible ambiguity here");
```

```
Set(Tint=>Red); -- Set(Red) is ambiguous.
Set(Signal=>Red); -- Red can denote either
Set(Color'(Red)); -- a Color or a Light
```

Ada — Userdefined Operators

```
function "+" (Left,Right:Matrix) return Matrix;
function "+" (Left,Right:Vector) return Vector;
```

```
-- assuming that A, B, and C are of
-- the type Vector the following two
-- statements are equivalent:
```

```
A := B + C;
A := "+"(B, C);
```

Readings and References

📖 [Read Scott, pp. 117–123, 428–433](#)

Summary

- Each procedure call pushes a new activation record on the run-time stack. The AR contains local variables, actual parameters, a static (access) link, a dynamic (control) link, the return address, saved registers, etc.
- The frame pointer (FP) (which is usually kept in a register) points to a fixed place in the topmost activation record. Each local variable and actual parameter is at a fixed offset from FP.

Summary...

- The dynamic link is used to restore the FP when a procedure call returns.
- The static link is used to access non-local variables, i.e. local variables which are declared within a procedure which statically encloses the current one.