CSc 520

Principles of Programming Languages

39 : Scheme — Higher-Order Functions

Christian Collberg

collberg+520@gmail.com

Department of Computer Science

University of Arizona

Copyright © 2008 Christian Collberg

Higher-Order Functions

- A function is higher-order if
  1. it takes another function as an argument, or
  2. it returns a function as its result.
- Functional programs make extensive use of higher-order functions to make programs smaller and more elegant.
- We use higher-order functions to encapsulate common patterns of computation.

Higher-Order Functions: `map`

- Map a list of numbers to a new list of their absolute values.
- Here's the definition of `abs-list` from a previous lecture:

```
(define (abs-list L)
   (cond
      [(null?  L) '()]
      [else (cons (abs (car L))
                  (abs-list (cdr L)))]
   )
)

> (abs-list '(1 -1 2 -3 5))
(1 1 2 3 5)
```


Higher-Order Functions: `map`...

- This type of computation is very common.
- Scheme therefore has a built-in function

  `(map f L)`

  which constructs a new list by applying the function f to every element of the list L.

$$\texttt{(map f '(}e_1\ e_2\ e_3\ e_4\texttt{))} \Downarrow \texttt{((f }e_1\texttt{) (f }e_2\texttt{) (f }e_3\texttt{) (f }e_4\texttt{)))}$$

Higher-Order Functions: map...

- `map` is a higher-order function, i.e. it takes another function as an argument.

```
(define (addone a) (+ 1 a))

> (map addone '(1 2 3)
(2 3 4)

> (map abs '(-1 2 -3))
(1 2 3)
```


Higher-Order Functions: map...

- We can easily define `map` ourselves:

```
(define (mymap f L)
   (cond
      [(null? L) '()]
      [else
         (cons (f (car L)) (mymap f (cdr L)))]))

> (mymap abs '(-1 2 -3))
(1 2 3)
```


Higher-Order Functions: map...

- If the function takes n arguments, we give `map` n lists of arguments:

```
> (map string-append
          '("A" "B" "C") '("1" "2" "3"))
("A1" "B2" "C3")

> (map + '(1 2 3) '(1 2 3))
(list 2 4 6)

> (map cons '(a b c) '((1) (2) (3)))
((a 1) (b 2) (c 3))
```


Lambda Expressions

- A lambda-expression evaluates to a function:

```
(lambda (x) (* x x))
```

  `x` is the function's formal parameter.
- Lambda-expressions don't give the function a name — they're anonymous functions.
- Evaluating the function:

```
> ((lambda (x) (* x x)) 3)
9
```

Higher-Order Functions: `map`...

- We can use `lambda`-expressions to construct anonymous functions to pass to `map`. This saves us from having to define auxiliary functions:

```
(define (addone a) (+ 1 a))

> (map addone '(1 2 3)
(2 3 4)

> (map (lambda (a) (+ 1 a)) '(1 2 3))
(2 3 4)
```


Higher-Order Functions: `filter`

- The filter-function applies a predicate (boolean-valued function) `p` to all the elements of a list.
- A new list is returned consisting of those elements for which `p` returns `#t`.

```
(define (filter p L)
   (cond
      [(null? L) '()]
      [(p (car L))
            (cons (car L) (filter p (cdr L)))]
      [else (filter p (cdr L))]))

> (filter (lambda (x) (> x 0)) '(1 -2 3 -4))
(1 3)
```


Higher-Order Functions: `fold`

Consider the following two functions:

```
(define (sum L)
   (cond
      [(null? L) 0]
      [else (+ (car L) (sum (cdr L)))]))
(define (concat L)
   (cond
      [(null? L) "" ]
      [else (string-append (car L) (concat (cdr L)))]))

> (sum '(1 2 3))
6
> (concat '("1" "2" "3"))
"123"
```


Higher-Order Functions: `fold`...

- The two functions only differ in what operations they apply (+ vs. string-append, and in the value returned for the base case (0 vs. "").
- The `fold` function abstracts this computation:

```
(define (fold L f n)
   (cond
      [(null? L) n]
      [else (f (car L) (fold (cdr L) f n))]))

> (fold '(1 2 3) + 0)
6
> (fold '("A" "B" "C") string-append "")
"ABC"
```

Higher-Order Functions: `fold`

- In other words, `fold` folds a list together by successively applying the function `f` to the elements of the list `L`.

```
(apply f '(e1 e2 e3 e4)) ⇒
                    (f e1 (f e2 (f e3 e4)))
```