
CSc 520

Principles of Programming Languages

39 : Scheme — Higher-Order Functions

Christian Collberg

collberg+520@gmail.com

Department of Computer Science

University of Arizona

Copyright © 2008 Christian Collberg

Higher-Order Functions

- A function is **higher-order** if
 1. it takes another function as an argument, or
 2. it returns a function as its result.
- Functional programs make extensive use of higher-order functions to make programs smaller and more elegant.
- We use higher-order functions to encapsulate common patterns of computation.

Higher-Order Functions: map

- Map a list of numbers to a new list of their absolute values.
- Here's the definition of `abs-list` from a previous lecture:

```
(define (abs-list L)
  (cond
    [(null? L) '()]
    [else (cons (abs (car L))
                  (abs-list (cdr L)))]
  )
)
```

```
> (abs-list '(1 -1 2 -3 5))
(1 1 2 3 5)
```

Higher-Order Functions: map...

- This type of computation is very common.
- Scheme therefore has a built-in function

$(\text{map } f \ L)$

which constructs a new list by applying the function **f** to every element of the list **L**.

$(\text{map } f \ '(e_1 \ e_2 \ e_3 \ e_4))$

$\Downarrow$

$((f \ e_1) \ (f \ e_2) \ (f \ e_3) \ (f \ e_4))$

Higher-Order Functions: map...

- map is a **higher-order function**, i.e. it takes another function as an argument.

```
(define (addone a) (+ 1 a))
```

```
> (map addone '(1 2 3))  
(2 3 4)
```

```
> (map abs '(-1 2 -3))  
(1 2 3)
```

Higher-Order Functions: map...

- We can easily define map ourselves:

```
(define (mymap f L)
  (cond
    [(null? L) '()]
    [else
     (cons (f (car L)) (mymap f (cdr L)))])
```

```
> (mymap abs '(-1 2 -3))
(1 2 3)
```

Higher-Order Functions: map...

- If the function takes n arguments, we give map n lists of arguments:

```
> (map string-append  
    '("A" "B" "C") '("1" "2" "3"))  
("A1" "B2" "C3")
```

```
> (map + '(1 2 3) '(1 2 3))  
(list 2 4 6)
```

```
> (map cons '(a b c) '((1) (2) (3)))  
((a 1) (b 2) (c 3))
```

Lambda Expressions

- A **lambda-expression** evaluates to a function:

`(lambda (x) (* x x))`

`x` is the function's formal parameter.

- Lambda-expressions don't give the function a name — they're **anonymous functions**.
- Evaluating the function:

```
> ((lambda (x) (* x x)) 3)
9
```

Higher-Order Functions: map...

- We can use lambda-expressions to construct anonymous functions to pass to map. This saves us from having to define auxiliary functions:

```
(define (addone a) (+ 1 a))
```

```
> (map addone '(1 2 3))  
(2 3 4)
```

```
> (map (lambda (a) (+ 1 a)) '(1 2 3))  
(2 3 4)
```

Higher-Order Functions: `filter`

- The `filter`-function applies a predicate (boolean-valued function) `p` to all the elements of a list.
- A new list is returned consisting of those elements for which `p` returns `#t`.

```
(define (filter p L)
  (cond
    [(null? L) '()]
    [(p (car L))
     (cons (car L) (filter p (cdr L)))]
    [else (filter p (cdr L))]))
```

```
> (filter (lambda (x) (> x 0)) '(1 -2 3 -4))
(1 3)
```

Higher-Order Functions: fold

Consider the following two functions:

```
(define (sum L)
  (cond
    [(null? L) 0]
    [else (+ (car L) (sum (cdr L)))]))

(define (concat L)
  (cond
    [(null? L) "" ]
    [else (string-append (car L) (concat (cdr L)))]))
```

```
> (sum '(1 2 3))
```

```
6
```

```
> (concat '("1" "2" "3"))
```

```
"123"
```

Higher-Order Functions: fold...

- The two functions only differ in what operations they apply (+ vs. string-append, and in the value returned for the base case (0 vs. "").).
- The fold function abstracts this computation:

```
(define (fold L f n)
  (cond
    [(null? L) n]
    [else (f (car L) (fold (cdr L) f n))]))
```

```
> (fold '(1 2 3) + 0)
6
```

```
> (fold '("A" "B" "C") string-append "")
"ABC"
```

Higher-Order Functions: fold

- In other words, fold folds a list together by successively applying the function **f** to the elements of the list **L**.

$$(\text{apply } f \text{ ' } (e_1 \ e_2 \ e_3 \ e_4)) \Rightarrow \\ (f \ e_1 \ (f \ e_2 \ (f \ e_3 \ e_4)))$$