
Event Driven Programming with Graphical User Interfaces (GUIs) A Crash Course

© Rick Mercer

Graphical User Interfaces (GUIs)

Most apps provide services through GUIs




A Few Graphical Components

- To build an event-driven program with a graphical user interface (GUI)
 - Begin with a well-tested model such as
 - GameOfLife, GameTree, MineSweeper, Boggle
 - Layout graphical components to allow user interaction
 - Ensure the correct things happen for each *events* triggered by user interaction
 - user clicks a button, moves a mouse, presses the enter key, adjusts a slider bar, presses the escape key, clicks the mouse. Select a menu option, ...

A Few Graphical Components

- Java's graphical components include
 - windows, buttons, text areas, menus, dialog boxes, tables with sortable columns, trees to expand folders, tabbed panes, images, ...http://web.mit.edu/6.005/www/sp14/psets/ps4/java-6-tutorial/components.html



A few types from the swing package

• The javax.swing package has many graphical components

JFrame: window with title, border, menu, buttons

JButton: A component that can "clicked"

JLabel: A display area for a small amount of text

JTextField: Allows editing of a single line of text



Get a "window" to show itself

- Have a class extend javax.swing.JFrame
 - Your new class inherits all the methods and instance variables for putting a window on the computer
- Add a main method to call the constructor
- Layout Set up the GUI in the constructor
 - See program on the next slide




Can you see the window?

```
import javax.swing.*; // Lot of GUI components now visible
public class FirstGUI extends JFrame {
  public static void main(String[] args) {
    JFrame aWindow = new FirstGUI();
    // Tell the JFrame object to show itself
    aWindow.setVisible(true);
 public FirstGUI() {
     this.setTitle("Graffiti");
     this.setDefaultCloseOperation(JFrame. EXIT ON CLOSE);
```

Some JFrame messages

• Set the size and location of the window with

```
this.setSize(210, 175); // 200 pixels wide, 150 pixels tall
this.setLocation(75, 40); // Upper left corner at 75 40
```



Building Graphical Components

 Add these three graphical components to the "content pane" of the JFrame


```
private JLabel aLabel =
    new JLabel("Change with setText(String)");

private JTextArea textEditor =
    new JTextArea("You can edit this text ");

private JButton clickMeButton =
    new JButton("Nobody is listening to me");
```

Using Null Layout


• By default, **JFrame** objects have only five places where you can add components a 2nd add wipes out the 1st



- There are many layout strategies, we'll use null layout setLayout (null);
 - State there is no object to decide where components go
 - We must set each component's size and location

Add components to a window

• Add the previously constructed components to the center part of the **JFrame**



```
this.setLayout(null);
aLabel.setSize(180, 30);
aLabel.setLocation(5, 0);
add(aLabel);

textEditor.setSize(180, 60);
textEditor.setLocation(5, 35);
add(textEditor);
clickMeButton.setSize(180, 30);
clickMeButton.setLocation(5, 95);
add(clickMeButton);
```

Other useful methods

- String getText() get the text stored in COMPONENTS JButton JTextArea TextField
- void setText(String str) changes the text stored in JButton JTextArea JTextField
- Two messages wrap at the word level in a JTextArea default is NO wrapping

```
textEditor.setLineWrap(true);
textEditor.setWrapStyleWord(true);
```

Other useful methods

```
textEditor.setBackground(Color.CYAN);
textEditor.setFont(
    new Font("Courier", Font.BOLD, 24));
```

So what happens next?

- You can layout a pretty GUI
- You can click on buttons, enter text into a text field, move the mouse, press a key
 - And NOTHING happens

So let's make something happen ...

Java's Event Model

- Java and the operating system work together to detect user interaction
 - JButton objects are notified when clicked
 - JTextField and JTextArea objects with focus know when the user presses the enter key
 - A MouseListener object knows when the mouse is clicked, pressed, released, or enters/exits a component MouseListener is an interface
 - A **HyperLinkEventListener** object knows when the hyperlink has been clicked *HyperLinkEventListener* is an interface

Example: Action Events

- The buttons, text fields, and menu items do not perform the actions
 - Instead JButton, JTextField, JMenuItem objects send actionPerformed messages to other objects
- The code that responds to events is often located in actionPerformed methods
- We need to have a class that implements the ActionListener interface to guarantee the object has an actionPerformed message

How to Handle Events

- Add a private inner class that can listen to the event that the component generates
 - Your class must implement a listener interface to guarantee that it has the expected methods: First up:
 ActionListener
- Add the listener so the component can later send actionPerformed messages to the listener
 - Events occur anytime in the future--the listener is listening (waiting for user generated events such as clicking a button or entering text into a text field)

Have a class that implements ActionListener

```
Inner class to listen to events
private class ButtonListener implements ActionListener {
  // clickMeButton will call this method once registered (below)
 public void actionPerformed(ActionEvent anActionEvent) {
    // Show contents of the JTextArea
    JOptionPane.showMessageDialog(null, textEditor.getText());
  // In the constructor of the class that extends JFrame,
  // register the instance of the listener so the component
  // can later send messages to that object
 ButtonListener aListener = new ButtonListener();
  clickMeButton.addActionListener(aListener);
```

Caution: This is easy to forget. It is a bug, not a compile time error

Active Collaborative Learning

• In teams of 2 or 3, on one computer, implement an event-driven program with a GUI to toggle text and colors in a JTextArea with button clicks. Match the GUI

